

Art.Nr.: 1036

For special application in generating plants for monitoring and control of fuses of brushless excitation generating systems.
Dustsealed aluminium housing with aluminium front plate as plug-in unit for control board of generating plant with two separately controlled Hand Lamps, 360° phase shifter, easy to exchange fuse via external fuse holder, and signal "ON / OFF" switch.

General Data:

Light Source: 2 pcs. external hand lamp model 900.00 with flash bulb (control unit without built-in flash bulb)
Flash bulb: 4pin socket-mounted Xenon longlife, glass tube protected
Light intensity: max. 700 Lux in 50cm distance from reflector (beam axis)
Flash duration: approx. 2 - 7µs
Frequency range: mains frequency (50 or 60 Hz)
Trigger action: mains synchronization
Phase shifter: continuously adjustable by control knob from 0° to 360°

Technical Data:

Power supply: 230V AC, 50 to 60 Hz, 115V AC at request
Housing: aluminium case with two handles, two connection boxes
Dimensions: front: 340 x 175mm, depth: 110mm
Weight: approx. 2,4 kgs incl. Hand Lamps

MOVISTROB® 715.00-S/NSY-PH/2uHL



Accessories:

Spare flash bulbs
Handlamp Type 900.00
Protective Spectacles incl. case Type 950.01

